

# HS-2510W-2D / 2512W-2D



Specification	HS-2510W-2D	HS-2512W-2D
Processor	Intel Celeron J1900 CPU, Quad Core CPU, 2.0GHz/2.42GHz (Burst), 2M Cache	
System Memory	DDR3L 1333MHz, SO-DIMM x 1, max. 8GB	
Storage Device	SATA Storage x 2 (one for HDD/SSD, the other for 1" SSD only) or eMMC x 1	
Display	9.7" 1024 x 768 LCD panel	12" 1024 x 768 LCD panel
Touch	True-flat PCAP touch with multi-touch support (IP65 on front panel)	
Built-in Printer	2D barcode scanner	
Power Supply	12V DC power adaptor, 60W	12V DC power adaptor, 60W
OS Support	Windows 10 IoT/Windows Embedded 8.1 Industry/Windows 7/POSREADY 7/Linux per request	
<b>Connectivity</b>		
LAN Port	10/100/1000Mb x 1	
Serial Port	DB9 x 2 + RJ45 x 1 with 5V/12V support on COM1/COM2/COM3, RJ45 to DB9 cable optional	
Parallel Port	Yes	
Standard USB Port	4, 1 x USB 3.0/2.0 + 3 x USB 2.0	
Audio Port	Line out	
PS/2 Port	Yes	
VGA Port	D-SUB, 15 pins, with 12V support for Posiflex monitor	
CR Port	1, control 2 CR	
Mini-PCIe slot	Yes, for half size card	
<b>Physical Dimension</b>		
Dimension (W x D x H in mm)	224.5 x 185 x 387	297 x 187 x 402
Weight (N.W. in Kg)	4.2	5.3
<b>Environment</b>		
Operation Condition	0°C - 40°C, 20%RH - 90%RH (Equipped with HDD) ; 0°C - 50°C, 20%RH - 90%RH (Equipped with SSD)	
Storage Condition	-20°C - 70°C, 10%RH - 90%RH	
<b>Options</b>		
SSD	2.5" or 1" SATA SSD	
eMMC	16GB/32GB module	
MSR	Integrated with 3 track module (HID/VCOM Selectable)	
Smartcard Reader	Integrated	
RFID	Integrated, support MIFARE Ultralight and Classic 1K card (HID/VCOM Selectable)	
Finger Print Sensor	Integrated	
LM-6507	7" 800 x 480 rear-mount 2nd display for HS Series (USB interface)	
PD-6507	7" color graphical line display, rear-mount (USB interface)	
PD-2607UE	2 x 20 VFD, rear-mount, USB with Virtual COM support	
PD-340UE	2 x 20 LCD, rear-mount, USB with Virtual COM support	
WiFi	Internal mini-PCIe WiFi module with PIFA antenna	

\* The product information and specifications are subject to change without prior notice.  
 \* Please refer to the web site for more attachment options.

Taking Space Saving To Extreme



## HS-2510W-2D/2512W-2D Space Saving All-in-one POS Terminal

Certifications



Design and Manufacturing in Taiwan by Posiflex Technology Inc.  
 The product information and specifications are subject to change without prior notice.

2016Q1



POSIFLEX TECHNOLOGY INC.  
 No. 6, Wuquan Rd., Wugu Dist., New Taipei City 24886, Taiwan  
 Tel : +886-2-2299-1599 E-mail : sales@posiflex.com.tw  
 Fax : +886-2-2299-1819 www.posiflex.com

Authorized Distributor / Reseller

Inherits the compact concept of standard HS Series: Taking Space Saving to Extreme, the HS-2500W-2D Series comes with the 2D barcode scanner in place of the built-in thermal printer.



## Compact

The compact footprint of HS-2500W-2D Series makes itself adaptable to a wide range of counter styles and allows every inch of the work space usage to be optimized, thus creating maximum profit return for the store owners. This is what space saving is all about.

## All-in-one

As an "all-in-one" solution, HS-2500W-2D Series touch-screen terminal integrates some of the most widely used peripherals in daily POS operation, such as barcode scanner, MSR, smart card reader, finger print sensor and 2nd customer display, and has the features and functionality to cater for applications in retail, hospitality, health care, banking and more, while offering uncompromising performance.

## Aesthetics

Dressed from head to toe in timeless black or white color, the only trend that never goes out of style, and with stylish touches added throughout, HS-2500W-2D Series is not just a piece of machinery, it is an elegantly crafted piece of art that looks right at home in any store decoration.



2D barcode scanner



Optional built-in MSR smartcard reader, finger print sensor and RFID reader